

MORBARK® D 76 TRACK STUMP GRINDER



BENEFITS

- This powerful unit is equipped with an expandable rubber track undercarriage with 3.8 PSI ground pressure and an 76" boom arc for less positioning at the stump.
- 1 3/4" diameter piloted flange cutter head bearings increase bearing life and minimize exposure to dirt and debris.
- Multi-function wireless remote control with 50' tethered back-up remote provides full control of travel, cutter head, boom, e-stop and throttle functions while allowing the operator to stay clear of flying debris and get the best vantage point for operation.
- Like all Morbark equipment, the D 76 is a long-lasting, durable machine backed by a world-class parts and service support team.



Long Boom Technology

Knuckled boom allows maximum swing above and below grade to access hard-to-reach areas while maintaining full boom arc swing regardless of cutting depth.



Hydrostatic Drive

Hydrostatic primary drive with poly belt final drive and electronic cutting system brake provides efficient (90%) power transfer between drive and cutting system.



Boom Pivot Assembly

Heavy-duty boom pivot significantly reduces wear in critical area of the stump grinder to provide years of trouble-free service and allows for greater boom arm swing radius.



Expandable Track

Nachi Rubber Track Undercarriage with 3.8 PSI ground pressure is 72" long x 9" wide, turf-friendly and hydraulically expandable from 35" wide to 47" wide.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 5/14/12

General

Length	13'3"–14'
Width	35"–47"
Height	5'10"
Weight	4,880 lbs.
Engine	Kubota
Horsepower	66–84 HP
Fuel capacity	21 gallons
Hydraulic oil capacity	42 gallons
Boom arc swing	76"
Boom travel up	18"
Boom travel down	15"
Tracks	72" long x 9" wide
Primary drive	Hydrostatic
Secondary drive	Poly Chain
Cutter wheel speed	1,250 RPM

Equipment Highlights

Four-speed ground travel from 0–280 FPM with creep mode
 2" x 4" x 1/4" thick tubular steel frame construction
 12 cubic feet of chip retention
 Unit pre-plumbed for easy installation of plow assembly
 Hydraulic system includes: 2.48ci hydrostatic transmission, 8cc gear pump, 16cc track drive gear pump, 4.6ci hydraulic motor and Emmegi side-by-side radiator and hydraulic cooler package
 Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options

MultiTip Cutting System with 8 replaceable teeth
 Leonardi M1 Gold Cutting System with Rock Shock and 9 replaceable teeth
 New River Revolution Cutting System with 32 replaceable teeth
 Hillside Cutting System with Tomahawk hardware and 3 x 24 tooth pattern
 Hydraulic back-fill blade
 Custom paint and logo packages



MORBARK®
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

800.831.0042
 989.866.2381
www.morbark.com

PO Box 1000
 8507 S. Winn Rd.
 Winn, MI 48896