

# THE EAGLE HAS LANDED

Set your worries free and glide into the performance and durability of the Alamo Industrial® Eagle 15™ Flex-wing rotary mower. High-horsepower gearboxes, a thick deck design, and high blade tip speeds offer you the power to cut up to 3-1/2" diameter grass, weeds and brush. Cover more area in less time with the one brand that offers you over 40 years of on-the-job experience. The Eagle 15, landing at a dealer near you.



Eagle 15™

BUILT SHARPER™

# Eagle 15™

## Convenient Mount

Attached to the tractor using a level-lift drawbar hitch design, the unit is easily and conveniently mounted. A jack stand comes standard for proper storage of the unit when not in use as well as a safety tow chain.

## Safety In Mind

Standard double-row chainguards provide 2-layers of protection to help prevent material from being thrown out from under the machine.

## Durable Tires

Replaceable, puncture resistant, foam-filled airplane tires provide reliable movement of the unit and contribute to steady transport.

## Safely Transported

The unit may be moved down any standard road with ease with its 96" transport width. A newly designed safety lock is featured for additional protection during highway transport.

## Superior Power

The main driveline is CAT 5 constant velocity with CAT 5 wing drivelines featured with slip clutch protection against heavy shock loading.

A 235 HP divider coupled with 205 HP center and wing gearboxes provide the power you need to get through heavily vegetated areas with reliability. Routine maintenance is a snap with newly designed dipsticks featured on the wing gearboxes.



## Optimal Cutting Performance

A reinforced heavy duty steel pan blade carrier features (2) free-swinging 1/2" x 4" updraft blades capable of cutting up to 3-1/2" diameter grass, weeds and brush. Blade tip speeds have been increased now performing at a minimum of 16,286 FPM, which translates into better cutting performance for you.

A standard deck ring incorporates a round rolled flat bar ring welded to the underside of the deck preventing the blades from contacting the deck.



Replaceable skid shoes help protect the mower from damaging ground contact.

## Rugged Construction

An easy-clean 7-gauge deck made of heavy-duty steel and 1/4" x 10-1/2" replaceable, bolt-on side skirts promote durability and longer mower life.

## Level and Adjustment

A hydro-mechanical level lift system is featured for a uniform cut. The mower cutting height may be adjusted from 1/2" to 14-1/2" for your specific application. A spring-cushioned axle absorbs shock when unit is in motion.

## Additional Options

- Open or Closed Center Three-Spool Valve
- Valve Mounting Kit
- Winch & Stand
- Auxiliary Wheel Spindle Kit
- Special Paint
- 10' Model

## Requirements

Overall Width:  
186"  
Overall Length:  
183"  
Minimum Tractor HP  
Requirements:  
50 HP  
Gearbox Rating:  
Power Divider – 235 HP  
Center & Wings – 205 HP  
Material Cut Size:  
3-1/2" grass, weeds, & brush

Blade Tip Speed:  
Center  
540 RPM – 16,286 RPM  
1,000 RPM – 16,380 RPM  
Wings  
540 RPM – 16,415 RPM  
1,000 RPM – 17,137 RPM  
Output Shaft Diameter:  
2-3/8".  
Unit Shipping Weight:  
5,695 lbs.(Approx)



**ALAMO**  
INDUSTRIAL  
**BUILT SHARPER**  
A Member of Alamo Group

Alamo Industrial® | 1502 East Walnut Street, Seguin, TX 78155 | 800-882-5762 | www.alamo-industrial.com

© 2013 Alamo Group Inc. Registered trademarks identified are property of Alamo Group Inc.

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products. Warranty: Minimum one year parts and labor. Non-governmental users are subject to a modified policy. Only genuine Alamo Industrial parts may be used for warranty replacement.