

MORBARK® G 42 SP STUMP GRINDER



BENEFITS

- This powerful, lightweight and affordable stump grinder is ideal for modest landscapers and contractors, as well as rental stores.
- Its compact size and mobility allows it to be driven to sites that couldn't be reached with larger stump grinders.
- Generous 42" sweep allows the operator to grind more and move less.
- With a choice of three cutting system options, you can custom fit your grinder to best fits your needs. No other manufacturer offers their customers this many cutting system choices.
- Equipped with horsepower options of either 27 or 38 HP, this stump grinder really packs a punch.
- Like all Morbark equipment, the G 42 SP is a long-lasting, durable machine backed by a world-class parts and service support team.



4-up Fingertip Controls

Operator's control station with 4-up fingertip controls gives you complete control of the machine functions from one location.



Electric Clutch

Electronic clutch engagement with cutting system brake eliminates cumbersome belt tensing systems and increases operator safety.



Boom Pivot Assembly

Heavy-duty boom pivot is enhanced in critical areas for extended service life.



Clic™ Duals Option

Requiring no tools, Morbark's exclusive spring-loaded Clic™ Duals cut dual wheel removal and installation time in half versus bolt-on dual wheel configuration.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 5/14/12

General

Length	8'9"
Width (w/o dual wheels)	35"
Height	4'9"
Weight	1,620 lbs.
Engine	Kohler
Horsepower	27-38 HP
Fuel capacity	9 gallons
Hydraulic oil capacity	3 gallons
Boom arc swing	42"
Boom travel up	12 1/4"
Boom travel down	10 3/4"
Tires	(4) 5.70-8
Primary drive	V-Belt
Secondary drive	V-Belt
Cutter wheel speed	1,317 RPM

Equipment Highlights

Electronic cutter head engagement with electronic shut-down brake
 Two-speed ground travel from 0-188 FPM
 160cc hydraulic drive motor with 3:1 drive torque multiplier and hydraulic actuated parking brake with 3,700 in/lb of holding force
 1 3/4" diameter, 4140 hardened cutter head shaft with pillow block cutter head bearings
 Steel hood enclosure protecting hydraulic components, fuel and hydraulic reservoirs
 Oscillating front axle for stability over rough or uneven terrain
 3" square x 3/16" thick wall tubular steel frame structure
 (4) 5.70 x 8" tires

Additional Features

Hydraulic system with .33 ci dual displacement gear pump, four spool mono block control valve and geroler type drive motor
 Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options

Hillside Cutting System with Tomahawk hardware and 3 x 18 tooth pattern
 MultiTip Cutting System with 6 replaceable teeth
 Leonardi M1 Blue Shark cutting system
 Dual Wheel Package with spring-loaded Clic duals
 Custom paint and logo packages



MORBARK®
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

800.831.0042
 989.866.2381
www.morbark.com

PO Box 1000
 8507 S. Winn Rd.
 Winn, MI 48896