

SPECIFICATIONS WRIGHT Z™



	48"	52"	61"	
MOWER	Cutting Height Range	1.5" - 5.5"	1.5" - 5.5"	1.5" - 5.5"
	Deck Lift System	Foot Pedal Operated	Foot Pedal Operated	Foot Pedal Operated
	Deck Construction Heavy-Duty Commercial Fabricated	7 Gauge	7 Gauge	7 Gauge
	Blades (1/4" thick, high-lift wings)	(3) 16.5"	(3) 18"	(3) 21"
	Blade Tip Speed fpm at 3,584 rpm	19,000	19,000	19,000
	Spindles	Cast Iron Housing	Cast Iron Housing	Cast Iron Housing
	Blade Clutch/ Brake Maintenance-Free, Rated Heavy Duty	WARNER	WARNER	WARNER
	Discharge Systems	Side, Rear & Mulch	Side, Rear & Mulch	Side, Rear & Mulch
ENGINE	Makes Available	KAWASAKI	KAWASAKI	KAWASAKI
	Horsepower	27 (FX)	27 (FX), 31 (FX)	31 (FX)
	Cylinders	2	2	2
	Starting	Electric	Electric	Electric
	Hour Meter	Digital, Service Alert™	Digital, Service Alert™	Digital, Service Alert™
		27 & 31 HP equipment with heavy duty air cleaner		
TRACTOR	Operator Controls	Over the Lap Controls	Over the Lap Controls	Over the Lap Controls
	Hydro Pumps	HYDRO-GEAR™ 16 cc	HYDRO-GEAR™ 16 cc	HYDRO-GEAR™ 16 cc
	Wheel Motors	HYDRO-GEAR™ 15 cu in.	HYDRO-GEAR™ 15 cu in.	HYDRO-GEAR™ 15 cu in.
	Fuel Capacity	15 Gal.	15 Gal.	15 Gal.
	Drive Tires	24 x 9.5 - 12 (4 ply)	24 x 9.5 - 12 (4 ply)	24 x 12 - 12 (4 ply)
	Flat Free Caster Tires	13 x 5.0 - 6	13 x 5.0 - 6	13 x 6.5 - 6
	Speed Forward (mph)	13	13	13
	Speed Reverse (mph)	7	7	7
DIMENSIONS	Overall Length	78"	78"	78"
	Overall Width Deflector Up (Down)	49" (61")	53" (65")	62" (74")
	Dry Weight (lbs.)	940	950	985

All specifications subject to change without notice.

Warranty 2-year Limited Warranty: Covers parts and labor. For further details, see your local Wright dealer. To find the name of your nearest dealer, please visit www.wrightmfg.com.

COMING SOON TO A WRIGHT DEALER NEAR YOU!

For more information, call 1.130.360.9810 or find our dealer locator at www.wrightmfg.com.

THE WRIGHT WAY TO MOW

