SPECIFICATIONS

WRIGHT ZTO





		48"	52"	61"
	Cutting Height Range	1.5 - 5.5"	1.5 - 5.5"	1.5 - 5.5"
	Deck Lift System	Pedal-Operated	Pedal-Operated	Pedal-Operated
MOWER	Deck Construction Aero Core™	7 Gauge	7 Gauge	7 Gauge
2	Blade Tip Speed (fpm at 3584)	19,000	19,000	19,000
	Spindles 1" Shaft with precision ball bearings	Cast Iron Housings	Cast Iron Housings	Cast Iron Housings
	Discharge Systems	Side, Rear & Mulch	Side, Rear & Mulch	Side, Rear & Mulch
	Models Available	Kawasaki FX/BS Cyclonic	Kawasaki FX/BS Cyclonic	Kawasaki FX/BS Cyclonic
	Horsepower	22/24	22/26	23.5/30
I CONT	Engine Rating System	SAE J1995/SAE J1940	SAE J1995/SAE J1940	SAE J1995/SAE J1940
	Starting	Electric	Electric	Electric
	Hour Meter	Digital / Reminders	Digital / Reminders	Digital / Reminders
	Operator Controls	Over-the-Lap Levers™	Over-the-Lap Levers™	Over-the-Lap Levers™
	Hydro Transmission	3400 Series	3400 Series	3400 Series
2	Fuel Capacity	14.5 Gal.	14.5 Gal.	14.5 Gal.
un acion	Drive Tires	23 x 10.5 - 12	23 x 10.5 - 12	23 x 10.5 - 12
	Caster Tires	13 x 5.0 - 6 Flat Free	13 x 5.0 - 6 Flat Free	13 x 5.0 - 6 Flat Free
	Speed Forward (mph)	10.5	10.5	10.5
	Speed Reverse (mph)	4	4	4
2	Overall Length	78"	78"	78"
DIMENSIONS	Overall Width Deflector Up (Down)	49" (59")	53" (63")	62" (72")
	Dry Weight (lbs)	1015	1025	1060

Warranty 2-year Limited Warranty: Covers parts and labor.

For further details, see your local Wright dealer.

To find the name of your nearest dealer, please visit www.wrightmfg.com.

AVAILABLE NOW AT A WRIGHT DEALER NEAR YOU!

For more information, call 1.301.360.9810 or find our dealer locator at www.wrightmfg.com.

THE WRIGHT WAY TO MOW.

